

Specifications

GP PowerBank – Premium Series



	PowerBank U-Smart	PowerBank Smart 2	PowerBank Travel	PowerBank Rapid 2
Model Number	GPPB13	GPPB14	GPPB03	GPPB16
Charging Time	~30 mins	~1 hour	2-5 hours	2-5 hours
Charging Channel	4 Channels	4 Channels	4 Channels	2 Channels
Configuration	Corded Type	Corded Type	Corded Type	Plug-in Type
Input Voltage	100-240V AC 50/60Hz 12V DC	100-240V AC 50/60Hz 12V DC	100-240V AC 50/60Hz 12V DC	100-240V AC 50/60Hz
Output Voltage	DC 12V 2.5A	DC 12V 1.5A	DC 1.6V 2050mA	DC 3.2V 1050mA
Battery Type	NiMH	NiMH/NiCd	NiMH	NiMH
Battery Size	AA/AAA	AA/AAA	AA/AAA	AA/AAA
Car Charging Function	√	√	√	-
Charging Current				
- AA	NiMH - 3400mA	NiMH - 2000mA NiCd - 1000mA	1-2 pcs - 1025mA 3 pcs - 683mA 4 pcs - 512.5mA	2 pcs - 1050mA 4 pcs - 525mA
- AAA	NiMH - 1700mA	NiMH - 1000mA NiCd - 400mA	1 - 2 pcs - 425mA	2 pcs - 525mA
Trickle Charge	√	√	√	√
Termination Method				
- Minus Delta Voltage (-dV)	Individual	Individual	Individual	√
- Safety Timer	Individual	Individual	Individual	√
- Temperature Protection	Individual	Individual	√	√
- Alkaline Battery Detection	√	√	√	√
- Damaged Battery Detection	√	√	√	√
LED Indicator	Dual Color x 4	Red x 4	Dual Color x 1	Dual Color x 1
Safety Approval	CE/GS/UL/FCC/SAA/ e-Mark	CE/GS/UL/FCC/ SAA/e-Mark	CE/GS/UL/e-Mark	CE/GS/UL
Dimension (L) x (W) x (T) mm	120 x 74 x 47	119.5 x 85 x 31.5	108.3 x 66.3 x 28.7	115.5 x 69.5 x 31.9