

Specifications

GP PowerBank – Specialty Series



	PowerBank Specialty	PowerBank Audio	PowerBank Torch 4-in-1
Model Number	GPPB09	GPPB12	GPPB18
Charging Time	~10 hours	1 pc ~2 hours 2 pcs ~4 hours	~12.5 hours
Charging Channel	2 Channels	1 Channel	1 Channel
Configuration	Plug-in Type	Plug-in Type	Plug-in Type
Input Voltage	230V AC 50Hz (GS/BS) 120V AC 60Hz (UL)	230V AC 50Hz (GS/BS) 120V AC 60Hz (UL)	230V AC 50Hz (GS/BS) 120V AC 60Hz (UL)
Output Voltage	DC 9.8V	DC 2.8V	DC 5.6V 250mA
Battery Type	NiMH	NiMH	NiMH
Battery Size	9V	Prismatic (14M)/AA	AA
Charging Current			
- D NiMH	-	-	-
- C NiMH	-	-	-
- AA NiMH	-	700mA	250mA (Rated)
- AAA NiMH	-	-	-
- 9V NiMH	24mA	-	-
- Prismatic NiMH (14M)	-	700mA	-
Trickle Charge	-	√	-
Termination Method			
- Minus Delta Voltage (-dV)	-	√	-
- Safety Timer	-	√	-
- Temperature Protection	-	-	-
- Alkaline Battery Detection	-	√	-
- Damaged Battery Detection	-	√	-
LED Indicator	Green x 2	Dual Colour x 2	Green x 1
Safety Approval	CE/GS/UL	CE/GS/UL	CE/GS/UL
Dimension (L) x (W) x (T) mm	98.6 x 66.2 x 60.0	127 x 82 x 42.6	198 x 53.5 x 34